

STEELFLOW

Unvented Cylinders

Manufactured From Stainless Steel



McDonald
Water Storage
Hot Water Storage Solutions

STEELFLOW

Stainless Steel Unvented Hot Water Cylinder Range

McDonald Water Storage is synonymous with superior quality hot water cylinders and our STEELflow range of stainless steel unvented cylinders is no exception.

Manufactured from premium grade duplex stainless steel ensuring superior corrosion resistance, STEELflow provides uncompromising efficiency and high quality standards, with a range of high performance cylinders for those on a budget.

CONTENTS

General Information
STEELflow Direct
STEELflow Direct Slimline
STEELflow Indirect
STEELflow Indirect Slimline
STEELflow Direct Solar
STEELflow Indirect Solar
STEELflow Heat Pump
STEELflow Heat Pump
Slimline
STEELflow Tank on Tank
STEELflow Indirect
Pre-plumbed
STEELflow Heat Pump
Pre-plumbed
STEELflow Tank on Tank
Pre-plumbed



Discover The Benefits Of The **STEELflow** Unvented Range

- Premium grade duplex stainless steel providing superior performance
- Direct and Indirect models 60 - 300 litres, Solar Direct, Solar Indirect and Heat Pump models 150 - 300 litres
- Pre-plumb options available on Direct, Indirect and Heat Pump models
- Compression fittings and 90 degree elbow on hot water draw off as standard for ease of installation
- External expansion for ease of servicing
- Proven reliability with 25 year guarantee



Why **STEELflow**?



Our STEELflow products are manufactured to the highest specification, with superior quality raw materials and components. They come with a manufacturers guarantee and fully tested to ensure they are compliant with the latest standards and regulations.

One of the STEELflows key advantages is the efficient heat transfer of the corrugated coil with increased surface area when compared to plain tube, ensuring faster reheat times, improving efficiency and reducing ongoing costs.

The automated welding procedures with post weld pickling and passivating treatment guarantees the strength of the welds.

All In One Box

The Perfect Installation Solution

COMPONENT	Direct	Indirect	Solar Direct	Solar Indirect	Heat Pump
Inlet Combination Control Set incorporating (Supplied) - Pressure Reducing Valve set at 3 Bar - Balanced Cold Feed set at 3 Bar - Expansion Relief Valve set at 6 Bar	●	●	●	●	●
Temperature and Pressure Relief Valve 7 Bar/95°C (Fitted)	●	●	●	●	●
Tundish (Supplied)	●	●	●	●	●
3kW Immersion Heater - Primary Heat Source (Fitted)	●				
3kW Immersion Heater - Back Up Heat Source (Fitted)	●	●	●	●	●
Expansion Vessel (Supplied)	●	●	●	●	●
Dual Control and Overheat Thermostat (Supplied)		●		●	
Single High Limit Thermostat (Supplied)			●	●	●
Two Port Motorised Zone Valve (Supplied)		●		●	●

The STEELflow range is supplied with all the necessary components required to install the unit.

Compression fittings are supplied fitted on all the STEELflow cylinders to provide a quicker installation process and reduce additional cost on installation.

In addition, a 90 degree elbow has been added to the hot water draw off on all models, not only reduce installation time but also negate any damage caused by solder flux above the connection.

The table opposite shows what other components are included (supplied or fitted) with your STEELflow cylinder, dependant on model.

Guide To Specification

As a general principal, when sizing the cylinder for a typical domestic property, each occupant of the property will require between 35 and 45 litres of hot water per day.

The table opposite provides a guideline to the cylinder size required. When specifying a solar or heat pump cylinder, take in to consideration the availability of the renewal energy input.

PROPERTY SIZE	Indirect	Direct
1 bedroom + bath/shower	90/120	120/150
2 bedroom + bath/shower	150	170
3 bedroom + bath/shower	170	200
4 bedroom + bath/shower	200/250	250/300

STEELFLOW

Direct Models

The STEELflow direct unvented cylinder is manufactured from duplex stainless steel, and specifically designed for use with mains electricity.

The direct model is supplied complete with two immersions. This allows for one to be utilised for on-peak use and where available, one for off-peak use. This provides the flexibility to heat the store of water utilising off-peak electricity, making the unit extremely efficient.

There are 7 model sizes available, ranging from 90 litres to 300 litres, with pre-plumb options available.



COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- T&P Valve (1/2" Female)
- Immersion Heaters (1 3/4" Female) (2 immersion heaters in 120L models and above)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- Tundish

KEY BENEFITS

- High Grade Duplex Stainless Steel
- 25 Year Guarantee
- Post weld treatment for maximum durability
- Low heat losses
- Drain valve supplied as standard
- High Density Foam Insulation
- Optional Titanium immersions available

Product Stock Code		CCS90D	CCS120D	CCS150D	CCS170D	CCS200D	CCS250D	CCS300D
Capacity (Litres)		90	120	150	170	200	250	290
Height (mm)		707	894	1081	1209	1399	1711	1930
Diameter (mm)		545	545	545	545	545	545	545
Approximate Weight (KG)	Empty	19	23	27	31	35	40	45
	Full	109	143	177	201	235	290	335
Standing Heat Loss	Watts	46	50	55	68	71	83	94
	kW/24hr	1.10	1.20	1.32	1.63	1.70	1.99	2.26
ErP Class		C	C	C	C	C	C	C
Load Profile		M	M	M	L	L	XL	XL

Direct Slimline Models

The STEELflow direct slimline unvented cylinder is manufactured from duplex stainless steel, and specifically designed for use with mains electricity. The slimline range has a 475mm diameter, perfect for space restricted installations.

The direct model is supplied complete with two immersions. This allows for one to be utilised for on-peak use and where available, one for off-peak use. This provides the flexibility to heat the store of water utilising off-peak electricity, making the unit extremely efficient.

There are 6 model sizes available, ranging from 60 litres to 200 litres.

COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- T&P Valve (1/2" Female)
- Immersion Heaters (1 3/4" Female) (2 immersion heaters in 120L models and above)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- Tundish

KEY BENEFITS

- 475mm diameter for restricted space availability
- High grade duplex stainless steel
- 25 Year guarantee
- Post weld treatment for maximum durability
- Low heat losses
- Drain valve supplied as standard
- High density foam insulation
- Optional titanium immersions available

Product Stock Code		CCS60DSL	CCS90DSL	CCS120DSL	CCS150DSL	CCS170DSL	CCS200DSL
Capacity (Litres)		60	90	120	150	170	200
Height (mm)		685	947	1219	1482	1660	1928
Diameter (mm)		475	475	475	475	475	475
Approximate Weight (KG)	Empty	20	21	25	29	33	37
	Full	80	111	145	179	203	237
Standing Heat Loss	Watts	43	48	57	67	71	75
	kW/24hr	1.02	1.14	1.37	1.60	1.70	1.80
ErP Class		C	C	C	C	C	C
Load Profile		M	M	M	M	M	L



STEELFLOW

Indirect Models

The STEELflow indirect unvented cylinder is manufactured from duplex stainless steel, and specifically designed for use with a conventional gas or oil boiler.

The high efficiency corrugated coil heat exchanger, connected to a boiler, heat the full volume of water held within the cylinder. The coil's corrugated design provides faster recovery times than plain coils due to the increased surface area.

There are 7 model sizes available, ranging from 90 litres to 300 litres, with pre-plumb options available.

All models are supplied with an on-peak back-up immersion.

Pre-plumb options available

COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- Secondary Return 200-300 litre (22mm compression)
- T&P Valve (1/2" Female)
- Thermostat Pocket
- Immersion Heater (1 3/4" Female)
- Boiler Coil Flow / Return (22mm compression)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- 2 Port Valve
- Tundish
- Dual Control and Overheat Thermostat

KEY BENEFITS

- High Grade Duplex Stainless Steel
- 25 Year Guarantee
- Corrugated coil for maximum heat transfer
- Post weld treatment for maximum durability
- Low heat losses
- Drain valve supplied as standard
- High Density Foam Insulation

Product Stock Code		CCS90I	CCS120I	CCS150I	CCS170I	CCS200I	CCS250I	CCS300I
Capacity (Litres)		88	118	147	167	197	247	287
Height (mm)		707	894	1081	1209	1399	1711	1930
Diameter (mm)		545	545	545	545	545	545	545
Approximate Weight (KG)	Empty	20	24	28	32	36	41	46
	Full	108	142	175	199	233	288	333
Standing Heat Loss	Watts	46	50	55	68	71	83	94
	kW/24hr	1.10	1.20	1.32	1.63	1.70	1.99	2.26
ErP Class		C	C	C	C	C	C	C



Indirect Slimline Models

The STEELflow indirect unvented cylinder is manufactured from duplex stainless steel, and specifically designed for use with a conventional gas or oil boiler. The slimline range has a 475mm diameter, perfect for space restricted installations.

The high efficiency corrugated coil heat exchanger, connected to a boiler, heat the full volume of water held within the cylinder. The coil's corrugated design provides faster recovery times than plain coils due to the increased surface area.

There are 6 model sizes available, ranging from 60 litres to 200 litres.

All models are supplied with an on-peak back-up immersion.

COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- Secondary Return 200-300 litre (22mm compression)
- T&P Valve (1/2" Female)
- Thermostat Pocket
- Immersion Heater (1 3/4" Female)
- Boiler Coil Flow / Return (22mm compression)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- 2 Port Valve
- Tundish
- Dual Control and Overheat Thermostat

KEY BENEFITS

- 475mm diameter for restricted space availability
- High grade duplex stainless steel
- 25 Year guarantee
- Corrugated coil for maximum heat transfer
- Post weld treatment for maximum durability
- Low heat losses
- High density foam insulation

Product Stock Code		CCS60ISL	CCS90ISL	CCS120ISL	CCS150ISL	CCS170ISL	CCS200ISL
Capacity (Litres)		58	88	118	147	167	197
Height (mm)		685	947	1219	1482	1660	1928
Diameter (mm)		475	475	475	475	475	475
Approximate Weight (KG)	Empty	20	21	25	29	33	37
	Full	80	111	145	179	203	237
Standing Heat Loss	Watts	43	48	57	67	71	75
	kW/24hr	1.02	1.14	1.37	1.60	1.70	1.80
ErP Class		C	C	C	C	C	C



Direct Solar Models

The STEELflow direct solar unvented cylinder is manufactured from duplex stainless steel, designed to heat the store with solar thermal input in addition to two 3kW immersion heaters.

It has a high efficiency corrugated coil heat exchanger, which is connected to the solar thermal panels providing high heat transfer and with the back up facility of the 3kW immersion heaters. The coil's corrugated design provides faster recovery times than plain coils due to the increased surface area.

There are 5 model sizes available, ranging from 150 litres to 300 litres.



COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- Secondary Return 200-300 litre (22mm compression)
- T&P Valve (1/2" Female)
- Thermostat Pocket
- 2 Immersion Heaters (1 3/4" Female)
- Solar Coil Flow / Return (22mm compression)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- 2 Port Valve
- Tundish
- High Limit Thermostat

KEY BENEFITS

- High grade duplex stainless steel
- 25 Year guarantee
- Corrugated coil for maximum heat transfer
- Post weld treatment for maximum durability
- Low heat losses
- High density foam insulation

Product Stock Code		S150DS	S170DS	S200DS	S250DS	S300DS
Capacity (Litres)		147	167	197	247	287
Height (mm)		1081	1209	1399	1711	1930
Diameter (mm)		545	545	545	545	545
Approximate Weight (KG)	Empty	28	32	36	41	46
	Full	175	199	233	288	333
Standing Heat Loss	Watts	55	68	71	83	94
	kW/24hr	1.32	1.63	1.70	1.99	2.26
ErP Class		C	C	C	C	C
Solar Dedicated Volume (Ltr)		50	56	66	83	100



STEELFLOW

Indirect Solar Models

The STEELflow indirect unvented cylinder is manufactured from duplex stainless steel, and specifically designed for use with a conventional gas or oil boiler.

It has a high efficiency corrugated coil heat exchanger, which is connected to a boiler and the solar thermal panels providing high heat transfer and with the back up facility of the 3kW immersion heater. The coil's corrugated design provides faster recovery times than plain coils due to the increased surface area.

There are 5 model sizes available, ranging from 150 litres to 300 litres.

COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- Secondary Return 200-300 litre (22mm compression)
- T&P Valve (1/2" Female)
- Thermostat Pocket
- Immersion Heater (1 3/4" Female)
- Boiler Coil Flow / Return (22mm comp.)
- Solar Coil Flow / Return (22mm comp.)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- 2 Port Valve
- Tundish
- High Limit Thermostat
- Dual Control and Overheat Thermostat

KEY BENEFITS

- High Grade Duplex Stainless Steel
- 25 Year Guarantee
- Corrugated coil for maximum heat transfer
- Post weld treatment for maximum durability
- Low heat losses
- High Density Foam Insulation

Product Stock Code		S150IS	S170IS	S200IS	S250IS	S300IS
Capacity (Litres)		145	165	195	245	285
Height (mm)		1081	1209	1399	1711	1930
Diameter (mm)		545	545	545	545	545
Approximate Weight (KG)	Empty	29	33	37	42	47
	Full	174	198	232	287	332
Standing Heat Loss	Watts	55	68	71	83	94
	kW/24hr	1.32	1.63	1.70	1.99	2.26
ErP Class		C	C	C	C	C
Solar Dedicated Volume (Ltr)		50	56	66	83	100



STEELFLOW

Heat Pump Models

The STEELflow heat pump unvented cylinder is manufactured from duplex stainless steel, and specifically designed for use with either air source or ground source heat pumps.

It has a high efficiency corrugated coil heat exchanger, to heat the full volume of water held within the cylinder. The coil's corrugated design provides high heat transfer and flow rates from the heat pump, with faster recovery times than plain coils due to the increased surface area.

There are 5 model sizes available, 150 litres to 300 litres, with pre-plumb options available. All models are supplied with an immersion to boost the temperature and also provide back-up.

Pre-plumb options available

COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- Secondary Return 200-300 litre (22mm compression)
- T&P Valve (1/2" Female)
- Thermostat Pocket
- Immersion Heater (1 3/4" Female)
- Heat Pump Coil Flow / Return (1" Female)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- 2 Port Valve
- Tundish
- High Limit Thermostat

KEY BENEFITS

- High Grade Duplex Stainless Steel
- 25 Year Guarantee
- Corrugated coil for maximum heat transfer
- Post weld treatment for maximum durability
- Low heat losses
- High Density Foam Insulation
- Pressure loss on heat pump coils less than 0.4 bar

Product Stock Code		CCS150HP	CCS170HP	CCS200HP	CCS250HP	CCS300HP
Capacity (Litres)		142	162	189	239	279
Height (mm)		1081	1209	1399	1711	1930
Diameter (mm)		545	545	545	545	545
Approximate Weight (KG)	Empty	31	35	40	45	50
	Full	173	197	229	284	329
Standing Heat Loss	Watts	55	68	71	83	94
	kW/24hr	1.32	1.63	1.70	1.99	2.26
ErP Class		C	C	C	C	C
Surface Area HP Coil (m ²)		2	2	3	3	3



Heat Pump Slimline Models

The STEELflow heat pump unvented cylinder is manufactured from duplex stainless steel, and specifically designed for use with either air source or ground source heat pumps. The slimline range has a 475mm diameter, perfect for space restricted installations.

It has a high efficiency corrugated coil heat exchanger, to heat the full volume of water held within the cylinder. The coil's corrugated design provides high heat transfer and flow rates from the heat pump.

There are 3 model sizes available, 150 litres to 200 litres, with pre-plumb options available. All models are supplied with an immersion to boost the temperature and also provide back-up.



COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- Secondary Return 200-300 litre (22mm compression)
- T&P Valve (1/2" Female)
- Thermostat Pocket
- Immersion Heater (1 3/4" Female)
- Heat Pump Coil Flow / Return (1" Female)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- 2 Port Valve
- Tundish
- High Limit Thermostat

KEY BENEFITS

- 475mm diameter for restricted space availability
- High Grade Duplex Stainless Steel
- 25 Year Guarantee
- Corrugated coil for maximum heat transfer
- Post weld treatment for maximum durability
- Low heat losses
- High Density Foam Insulation
- Pressure loss on heat pump coils less than 0.4 bar

Product Stock Code		CCS150HPSL	CCS170HPSL	CCS200HPSL
Capacity (Litres)		146	160	190
Height (mm)		1482	1660	1928
Diameter (mm)		475	475	475
Approximate Weight (KG)	Empty	34	37	41
	Full	180	197	231
Standing Heat Loss	Watts	67	71	75
	kW/24hr	1.60	1.70	1.80
ErP Class		B	C	C
Surface Area HP Coil (m²)		1.617	2.015	2.015



Heat Pump Tank on Tank Models

The STEELflow heat pump tank on tank is an unvented cylinder with incorporated buffer store, designed for use with either air source or ground source heat pumps.

It has a high efficiency corrugated coil heat exchanger provides high heat transfer and flow rates from the heat pump.

The 50 litre buffer store provides extra volume for the heating system. This allows the heat pump to work longer but less often, reducing cycling and increasing the efficiency.

There are 4 model sizes available, 150 litres to 225 litres.

Pre-plumb options available

COMPONENTS

- 90 Degree Elbow on Hot Water Draw Off (22mm compression)
- Secondary Return 200-225 litre (22mm compression)
- T&P Valve (1/2" Female)
- Thermostat Pocket
- Immersion Heater (1 3/4" Female)
- Heat Pump Coil Flow / Return (1" Female)
- Cold Feed (22mm compression)
- Inlet Combination Control Set
- Expansion Vessel with Fixing Kit
- 2 Port Valve
- Tundish
- High Limit Thermostat

KEY BENEFITS

- Incorporated 50 Litre Buffer Store
- High Grade Duplex Stainless Steel
- 25 Year Guarantee
- Corrugated coil for maximum heat transfer
- Post weld treatment for maximum durability
- Low heat losses
- High Density Foam Insulation
- Pressure loss on heat pump coils less than 0.4 bar

Product Stock Code		S150HPB	S170HPB	S200HPB	S225HPB
Capacity (Litres)		142	162	189	214
Height (mm)		1485	1603	1801	1955
Diameter (mm)		545	545	545	545
Approximate Weight (KG)	Empty	47	50	57	60
	Full	240	263	300	360
Standing Heat Loss	Watts	55	68	71	83
	kW/24hr	1.32	1.63	1.70	1.99
ErP Class		C	C	C	C
Surface Area HP Coil (m²)		2	2	3	3

Indirect Pre-plumbed

The STEELflow indirect pre-plumbed range provide the installer with a 'plug and play' solution, not only speeding up the installation process onsite, but also standardising the plumbing configuration between properties on the same developments.

The pre-plumbed models are an optional addition to the standard product range, with all the components fitted and tested in the factory.

There are 5 model sizes available, 150 litres to 300 litres.



COMPONENTS

- All units are supplied fitted with;
- Inlet Combination Control Set with cold feed pipe set up with filling loop
 - T&P Valve
 - Tundish
 - 15mm Air-Bleed Valve
 - Flexi-Hose c/w Isolator & Gauge (0-4 Bar)
 - 2-Port Zone Valve
 - Head Pump
 - Immersion Heater
 - Wiring Centre
 - Auto Bypass Valve
- All units are supplied with;
- Expansion Vessel with Fixing Kit
 - T&P Insulation Cover
 - Dual Control Thermostat

KEY BENEFITS

- Plug and Play solution
- Standardised plumbing configuration
- Quality components
- Reduces installation time onsite

Product Stock Code		S150IPP	S170IPP	S200IPP	S250IPP	S300IPP
Capacity (Litres)		147	167	197	247	287
Height (mm)		1081	1209	1399	1711	1930
Diameter (mm)		545	545	545	545	545
Approximate Weight (KG)	Empty	34	38	42	47	52
	Full	181	205	239	294	339
Standing Heat Loss	Watts	55	68	71	83	94
	kW/24hr	1.32	1.63	1.70	1.99	2.26
ErP Class		C	C	C	C	C

Heat Pump Pre-plumbed

The STEELflow heat pump pre-plumbed range provide the installer with a 'plug and play' solution, not only speeding up the installation process onsite, but also standardising the plumbing configuration between properties on the same developments.

The pre-plumbed models are an optional addition to the standard product range, with all the fantastic benefits but with components fitted and tested in the factory.

There are 5 model sizes available, 150 litres to 300 litres.

Please note the pump shown on the image opposite on the heat pump side is an optional extra.

COMPONENTS

- All units are supplied fitted with;
- Inlet Combination Control Set with cold feed pipe set up with filling loop
 - 8m head pump (Optional extra)
 - 28mm 3 Port Valve
 - Fill and flush valve
 - 0-4 bar pressure gauge
 - T&P Valve
 - Tundish
- All units are supplied with;
- Expansion Vessel with Fixing Kit
 - T&P insulation cover
 - High Limit Overheat Thermostat

KEY BENEFITS

- Plug and Play solution
- Standardised plumbing configuration
- Quality components
- Reduces installation time onsite

Product Stock Code		S150HPPP	S170HPPP	S200HPPP	S250HPPP	S300HPPP
Capacity (Litres)		142	162	189	239	279
Height (mm)		1081	1209	1399	1711	1930
Diameter (mm)		545	545	545	545	545
Approximate Weight (KG)	Empty	37	41	46	51	56
	Full	179	203	235	290	335
Standing Heat Loss	Watts	55	68	71	83	94
	kW/24hr	1.32	1.63	1.70	1.99	2.26
ErP Class		C	C	C	C	C
Surface Area HP Coil (m ²)		2	2	3	3	3

Heat Pump Tank on Tank Pre-plumbed

The STEELflow heat pump tank on tank pre-plumbed range provide the installer with a 'plug and play' solution, not only speeding up the installation process onsite, but also standardising the plumbing configuration between properties on the same developments.

The 50 litre buffer store provides extra volume for the heating system. This allows the heat pump to work longer but less often, reducing cycling and increasing the efficiency.

The pre-plumbed models are an optional addition to the standard product range, with all the fantastic benefits but with components fitted and tested in the factory.

There are 4 model sizes available, 150 litres to 225 litres.

Please note the pump shown on the image opposite on the heat pump side is an optional extra.

COMPONENTS

- All units are supplied fitted with;
- Inlet Combination Control Set with cold feed pipe set up with filling loop
 - 8m head pump (Heating)
 - 8m head pump (HP side optional extra)
 - 28mm 3 Port Valve
 - Fill and flush valve
 - 0-4 bar pressure gauge
 - T&P Valve and Tundish
 - Auto Air Vent
 - Heating System Isolation Valve
- All units are supplied with;
- Expansion Vessel with Fixing Kit
 - T&P insulation cover
 - High Limit Overheat Thermostat

KEY BENEFITS

- Plug and Play solution
- Standardised plumbing configuration
- Quality components
- Reduces installation time onsite

Product Stock Code		S150HPBPP	S170HPBPP	S200HPBPP	S225HPBPP
Capacity (Litres)		142	162	189	214
Height (mm)		1485	1603	1801	1955
Diameter (mm)		545	545	545	545
Approximate Weight (KG)	Empty	55	58	65	68
	Full	248	271	308	368
Standing Heat Loss	Watts	55	68	71	83
	kW/24hr	1.32	1.63	1.70	1.99
ErP Class		C	C	C	C
Surface Area HP Coil (m²)		2	2	3	3

Discover Our Complete Range Of Hot Water Storage Solutions

Open Vented and Combination Cylinders

Thermal Stores

Unvented Cylinders

Elson Replacement Solutions

Commercial Cylinders

Bespoke Design and Manufacture



For full details on a product range
click on the category above or
go to mcdonaldwaterstorage.com



McDonald Water Storage

Hot Water Storage Solutions

Pride in our
service, quality
and tradition



QUEENSWAY INDUSTRIAL ESTATE | GLENROTHES | FIFE | KY7 5QF

T: 01592 611123 | E: sales@mcdonaldwaterstorage.com

www.mcdonaldwaterstorage.com

